



### Carrier

<b>Make:</b>	Stewart & Stevenson
<b>Model:</b>	WTD-00350PB-79-160
<b>Type:</b>	Self propelled
<b>Depth:</b>	12,000'
<b>Engine:</b>	Caterpillar C13 440hp @ 2,100rpm
<b>Transmission:</b>	Caterpillar CX31-P600

### Mast

<b>Make:</b>	Stewart & Stevenson
<b>Height:</b>	79'
<b>Type:</b>	Internally guyed hydraulic telescopic single
<b>Rating:</b>	160,000lbs
<b>Max Hook Load:</b>	160,000lbs on 6 lines 110,000lbs on 4 lines
<b>Racking Capacity:</b>	Nil

### Drawworks

<b>Make:</b>	Crown
<b>Model:</b>	CE350DD
<b>Drums:</b>	Main & Sand line drums Sandline not installed
<b>Drill line:</b>	7/8"
<b>Brake:</b>	38" x 10" main 38" x 8" sand line
<b>Cooling system:</b>	Splash cooling
<b>Secondary brake:</b>	Single 40" pneumatic disc assist auxiliary brake

### Mud Pump / Mud Tank

<b>Engine:</b>	Detroit 14L Series 60 375hp @ 2,100rpm
<b>Transmission:</b>	Allison 4700 OFS
<b>Model:</b>	SJ Petro 300
<b>Max Pressure:</b>	5,000psi
<b>Capability:</b>	10.6bpm @ 1,250psi
<b>Mud Tank Volume:</b>	Total capacity 175bbl Main tank 150bbl Pill tank 25bbl

### Well Control System / Catwalk

<b>Spherical BOP:</b>	7 1/16" 5,000psi
<b>Gate BOP :</b>	7 1/16" 5,000psi double gate
<b>Accumulator Unit:</b>	6 station 66gal
<b>Pipehandler:</b>	Easternwell design automated hydraulic pipehandler operable @ 90° and 180° to well centre
<b>Maximum OD:</b>	5"
<b>Maximum Length:</b>	40'

1508052Q