

RIG 26

easternwell[™]
all together better



Carrier

Make:	Irontech SR242
Type:	5 Axle self-propelled workover rig
Depth:	13,000'
Engine:	Detroit Series 60 280kW @ 2,100rpm

Mast

Make:	Irontech	
Height:	104'	
Type:	Internally guyed hydraulic telescopic double	
Rating:	225,000lbs	
Max Hook Load:	Without Top Drive Rails 225,000lbs on 6 lines 200,000lbs on 4 lines	With Top Drive Rails 220,000lbs on 6 lines 195,000lbs on 4 lines

Top Drive

Make:	Bournedril Easternwell
Model:	TD75/3S - 5109
Torque:	9,000FT/LB

Drawworks

Drums:	Main & sand line drums
Model:	Irontech Rig Up
Drill Line:	1" 6 x 36
Sand Line:	5/16" 6 x 7-PC
Brakes:	42" x 10" main 38" x 8" sand line
Cooling System:	Splash cooling
Secondary Brake:	Double 47" pneumatic disc assist auxiliary brake

Mud Pump / Mud Tank

Engine:	Detroit Series 60 317kW @ 2,100rpm
Transmission:	Allison 4700 OFS
Model:	JWS 340
Max Pressure:	5,000psi
Capability:	6.69bpm @ 1,870psi
Mud Tank Volume:	Total Capacity 120bbl Main Tank 100bbl Pill Tank 20bbl
Shaker Tank:	Total Capacity 120bbl Suction tank 80bbl Settling tank 40bbl

Well Control

Spherical BOPs:	7 1/16" 5,000psi & 11" 3,000psi
Double Gate BOP:	7 1/16" 5 000psi & 11" 5,000psi
Accumulator Units:	4 Station 44gal & 6 Station 66gal
Pipe Handler:	Easternwell design automated hydraulic pipe handler
Maximum OD:	4"
Maximum Length:	40'